

600A AC DIGITAL CLAMP METER
CM-2000



AC / DC Voltage

AC Current

Resistance

Temp

Back light

Low Battery Indication

NCV

Torch

Diode

Continuity

Over Range Display

600V

FEATURES :

- ✓ 3½ DIGIT
- ✓ 1,999 COUNT
- ✓ JAW OPEN : 28 MM
- ✓ AUTO POWER OFF (APO)
- ✓ NON CONTACT VOLTAGE (NCV)
- ✓ TRUE RMS
- ✓ DATA HOLD

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1 mV	±0.5% of rdg ±5 digits
2V	1mV	
20V	10mV	
200V	100mV	
600V	1V	±1.0% of rdg ±5 digits

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1 mV	±1.5% of rdg ±10 digit
2V	1mV	±1.0% of rdg ±5 digits
20V	10mV	
200V	100mV	
600V	1V	±1.2% of rdg ±5 digits

RESISTANCE

RANGE	RESOLUTION	ACCURACY
200Ω	0.1Ω	±0.8% of rdg±5 digits
2kΩ	1Ω	±0.8% of rdg±1 digits
20kΩ	10Ω	
200kΩ	100Ω	
2MΩ	1kΩ	
20MΩ	10kΩ	±1.2% of rdg±5 digits

AC CURRENT

RANGE	RESOLUTION	ACCURACY
2A	1mA	±3.0% of rdg±5 digits
20A	10mA	
200A	100mA	
600A	1A	±2.0% of rdg±5 digits

TEMPERATURE

RANGE	RESOLUTION	ACCURACY
-40°C~1000°C	1°C	<400°C±(1.0% +5) digit ≥400°C±(1.5% +15) digit
0°F~1832°F	1°F	<750°F±(1.0% +5) digit ≥750°F±(1.5% +15) digit

POWER : 1.5V AAA x 2

Dimension	: H240 x W110 x D45 mm
Weight	: Approx. 200g.
Accessories	: Test leads, User Manual Carrying Bag & Battery.
Qty	: 40 Pcs. in a Box