

1000A AC/DC DIGITAL CLAMP METER
CM-2046



V≈

AC / DC Voltage

A≈

AC / DC Current

⚡

Diode

☀

Back light

🌡

Temp

🔋

Low Battery Indication

NCV

NCV

Ω

Resistance

💡

Torch

📶

Continuity

OL

Over Range Display

CAT III

600V

FEATURES :

- ✓ 3½ DIGIT
- ✓ 1,999 COUNT
- ✓ JAW OPEN : 52 MM
- ✓ AUTO POWER OFF (APO)
- ✓ TRUE RMS
- ✓ MAX / MIN / RELATIVE
- ✓ DATA HOLD
- ✓ AUTO / MANUAL RANGE

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1mV	±1.0% of rdg ±5 digits
2V	1mV	±0.5% of rdg ±5 digits
20V	10mV	
200V	100mV	
1000V	1V	±1.0% of rdg ±5 digits

DC CURRENT

RANGE	RESOLUTION	ACCURACY
200A	100mA	±2.0% of rdg±5 digits
1000A	1A	

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1mV	±1.5% of rdg ±5 digits
2V	1mV	±1.0% of rdg ±5 digits
20V	10m1V	
200V	100mV	
750V	1V	±1.5% of rdg ±5 digits

AC CURRENT

RANGE	RESOLUTION	ACCURACY
200A	100mA	±2.0% of rdg±5 digits
1000A	1A	

RESISTANCE

RANGE	RESOLUTION	ACCURACY
200Ω	0.1Ω	±0.8% of rdg±5 digits
2kΩ	1Ω	±0.8% of rdg±3 digits
20kΩ	10Ω	
200kΩ	100Ω	
2MΩ	1kΩ	
20MΩ	10kΩ	±1.2% of rdg±5 digits

POWER : 1.5V AAA x 2

Dimension	: H185 x W65 x D32 mm
Weight	: Approx. 200 g.
Accessories	: Test leads, Manual, TP04 Thermocouple, Carrying Bag & Battery.
Qty	: 30 Pcs. in a Box.