

LCR METER
LCR-4070



- Inductance
- Capacitance
- Resistance
- Compact
- Low Battery Indication
- OL Over Range Display
- Auto Power Off
- CAT II 600V

FEATURES :

- ✓ 3½ DIGITS
- ✓ 1,999 COUNTS
- ✓ INDUCTANCE MEASUREMENT : 0.1uH~20H
- ✓ CAPACITANCE MEASUREMENT : 0.1pH~2000uF
- ✓ RESISTANCE MEASUREMENT : 0.01Ω~20Ω
- ✓ LIGHT WEIGHT & COMPACT
- ✓ FULL PROTECTION FUNCTION
- ✓ CAPACITOR SELF DISCHARGE FUNCTION
- ✓ AUTO POWER OFF
- ✓ ZERO ADJUSTMENT TO OBTAIN ACCURATE MEASURING VALUE
- ✓ SAMPLING TIME : 0-5 SECONDS
- ✓ OVER LOAD RANGE SYMBOL "1"

CAPACITANCE

RANGE	RESOLUTION	ACCURACY
200pF	0.1pF	±(2.0%+5)
2nF	1pF	
20nF	10pF	
200nF	100pF	
2μF	1000pF	
20μF	0.01uF	
200μF	0.1uF	
2000μF	1μF	±(5.0%+5)

INDUCTANCE

RANGE	RESOLUTION	ACCURACY
200uH	0.1uH	±(3.0%+5)
2mH	1uH	±(2.0%+5)
20mH	10uH	
200mH	100uH	
2H	1mF	±(5.0%+5)
20H	10mF	

RESISTANCE

RANGE	RESOLUTION	ACCURACY
20Ω	0.01Ω	±(1.0%+5)
200Ω	0.1Ω	±(0.8%+2)
2KΩ	1Ω	
20KΩ	10Ω	
200KΩ	100Ω	
20MΩ	10KΩ	±(2.0%+5)

POWER : 9V (6F22) x 1

Dimension	: H185 x W93 x D35 mm
Weight	: Approx. 290g.
Accessories	: Test Lead, User Manual Carry case & Battery
Qty	: 30 Pcs. in a Box.