

MINI MOISTURE METER
MS-02



- Back light
- Data Hold
- MAX / MIN Function
- Ambient Humidity
- Auto Power Off
- Low Battery Indication

FEATURES :

- ☒ SINGLE POINT MEASUREMENT
- ☒ MULTI POINT AVERAGE MEASUREMENT
- ☒ DATA HOLD
- ☒ MAX / MIN VALUE
- ☒ AUTO POWER OFF
- ☒ AMBIENT TEMPERATURE MEASUREMENT
- ☒ ENVIRONMENT HUMIDITY MEASUREMENT
- ☒ MEASURES TEMPERATURE IN °C / °F
- ☒ MEASURES MOISTURE CONTENT OF WOOD / BUILDING MATERIAL
- ☒ BUILT IN CHARACTERISTIC OF 7 DIFFERENT KIND OF WOOD AND BUILDING MATERIAL

RED, ORANGE, GREEN TRICOLOUR BACK LIGHT

Automatically match the appropriate colour backlight according to the moisture content :

- RED BACKLIGHT :**
High moisture content, showing the letter W
- ORANGE BACKLIGHT :**
Moderate moisture content, showing the letter M
- GREEN BACKLIGHT :**
Low moisture content, showing the letter D

TECHNICAL SPECIFICATION

MOISTURE RANGE	Material A : 9.0%~57.0%±2.0%
	Material B : 7.0%~52.0%±2.0%
	Material C : 0.9%~23.0%±2.0%
	Material D : 0.0%~12.0%±2.0%
	Material E : 0.7%~9.0%±2.0%
	Material F : 0.5%~10.0%±2.0%
	Material G : 0.0%~17.0%±2.0%
ACCURACY	±2.0%
TEMPERATURE RANGE	-20°~60°C / -4°F~140°F
RESOLUTION	0.1°C / 1°F
ACCURACY	0.°C ~ 45°C ± 1.0°C others ±1.5°C 32°F ~ 113°F ± 2°F others ± 3°F
HUMIDITY	0.0% ~ 99.9% RH
RESOLUTION	0.1%RH
ACCURACY	20%~80% ±5.0% RH others ± 6.0% RH
Auto power off after 10 Mins. If necessary you can cancel the APO function.	

POWER : AAA 1.5 x 3

Dimension	: H138 x W56 x D25mm
Accessories	: Soft Carry Case, User Manual & Battery
Qty	: 50 Pcs. in a Box.