

MINI SOUND LEVEL METER  
SL-13A



- Back light
- Temperature
- RH Humidity Unit
- Data Hold
- Max / Min Measurement
- Fast / Slow Time Weighted
- Low Battery Indication
- Auto Power Off

- FEATURES :
- DATA HOLD
  - MAX/MIN VALUE
  - BACK LIGHT
  - FAST / SLOW TIME WEIGHTED SELECTION
  - TEMPERATURE UNIT SELECTION
  - AUTO POWER OFF
  - MEASURES SOUND LEVEL OF THE ENVIRONMENT
  - MEASURES TEMPERATURE & RELATIVE HUMIDITY

TECHNICAL SPECIFICATION

|                   |                                                                      |
|-------------------|----------------------------------------------------------------------|
| RANGE             | 30~130dBA                                                            |
| RESOLUTION        | 0.1 dBA                                                              |
| ACCURACY          | ± 1.5dB(94dB@1Khz) ± 5dB(94dB@8Khz)                                  |
| FREQUENCY         | 30Hz ~ 8KHz                                                          |
| DYNAMIC RANGE     | 50dB                                                                 |
| TIME WEIGHTING    | FAST : 125 ms,<br>SLOW : 1 Sec.                                      |
| MICROPHONE        | Electret condenser                                                   |
| TEMPERATURE RANGE | -20°~60°C / -4°F~140°F                                               |
| RESOLUTION        | 0.1°C / 1°F                                                          |
| ACCURACY          | 0.°C ~ 45°C ± 1.0°C others ±1.5°C<br>32°F ~ 113°F ± 2°F others ± 3°F |
| HUMIDITY          | 0.0% ~ 99.9% RH                                                      |
| RESOLUTION        | 0.1%RH                                                               |
| ACCURACY          | 20%~80% ±5.0% RH others ± 6.0% RH                                    |

|                     |                                          |
|---------------------|------------------------------------------|
| POWER : AAA 1.5 x 3 |                                          |
| Dimension           | : H142 x W58 x D28 mm                    |
| Accessories         | : Soft Carry Case, User Manual & Battery |
| Qty                 | : 50 Pcs. in a Box.                      |