

MTX-2
INDUSTRIAL PYROMETER



Performance with Precision



FEATURES :

- ✓ PRECISE NON-CONTACT MEASUREMENT
- ✓ °C OR °F SELECTION
- ✓ FAST, EASY & ACCURATE TEMPERATURE READING
- ✓ AUTOMATIC MEASUREMENT RANGE SELECTION
- ✓ ADJUSTABLE EMISSIVITY
- ✓ MAX / MIN RECORD
- ✓ BACKLIGHT LCD DISPLAY
- ✓ AUTOMATIC TRIGGER OFF
- ✓ BUILT IN LASER POINTER INCREASE THE TARGET ACCURACY
- ✓ DISTANCE SPOT RATIO (D:S) 13:1

Non Contact Temperature Measurement

Auto Polarity Display

Switchable unit

Data Hold

Colour LCD

Auto Power Off

MAX / MIN Record

Temperature Alarm

Adjustable Emissivity

TECHNICAL DATA :

RANGE	-50°C~580°C / -58°F~1076°F
ACCURACY	-50°C~0°C / -4°F~32°F:±4°C/7°F above 0°C/32°F:±2% of reading ±2°C/3.6°F
RESOLUTION	0.1°C~0.1°F
DISTANCE SPORT RATIO	13:1
EMITTANCE	ADJUSTABLE FROM 0.01~1.0
RESPONSE TIME	<500ms
RESPONSE SPECTRUM	8~14um
DIODE LASER	OUTPUT <1mW/630-670nm Level 2(II) Laser
AUTO POWER OFF	AROUND 25 SECOND
RELATIVE HUMIDITY	OPERATING : 10 TO 95% RH

POWER : 1.5V X 2 AAA BATTERY

Dimension	: H156 x W99 x D28 mm
Weight	: Approx. 176 Gms.
Accessories	: Soft Carry Case, User Manual & Battery
Qty	: 40 Pcs. in a Box.