

## **BK881** **Hi Efficiency Thermostatic 2 in 1 De-soldering Station** **& Soldering Station**

- Large Easy to Read Digital Display.
- Compact design. Lightweight handle, meet all kinds soldering demands. Extra de-soldering function makes work more efficient.
- 2 in 1 design with de-soldering and soldering work simultaneously. Save work space. Increase production volume and brings efficient manufacturing.
- Large LCD Display, compact, lightweight. LCD Display provides clear interface with the operator to adjust temperature and air level.
- Can be used for a variety of components such as QFP, SOP, PLCC or SOJ chips for de-soldering.
- Upgraded micro-computer control, digital adjustment and display.
- Auto protection for heating materials, which adopts Pulse Heating for better protection to heating elements, handle, and air nozzles which prolongs station life.
- ESD safe components avoid static damage.
- Auto Cooling to prevent heating components from overheating.
- Heats rapidly, stable temperature and high frequency.



### **Specifications**

|                     |                       |
|---------------------|-----------------------|
| Model               | BK881                 |
| Display             | LCD                   |
| Airflow Type        | Air bar Output        |
| Air volume          | 120L/Min.             |
| Dimension           | (L)150x(W)130x(H)99mm |
| Weight              | 2.5kg                 |
| Power Consumption   | 560W                  |
| Hot air temperature | 100~500°C             |
| Length              | 120cm                 |
| Weight              | 184g                  |
| Power Consumption   | 90W                   |
| Temp range          | 200~480°C             |
| Handle length       | 120cm                 |