

LS192

60° Gloss Meter, 1000GU

PART NO.
25621192



LS192 is a hand-held gloss meter with the universal 60° angle and a 0-1000GU range for paint, coating, metal, ceramics, stone and printed material. It measures without pressing a button, and results can be exported to Excel through the PC software.

KEY FEATURES

- Put-and-measure operation, no button press needed
- D65 light source for accurate measurements
- Precise measurement
- Dual mode: normal and QC
- Portable and smart
- Powerful PC software with Excel export

SPECIFICATIONS

Measuring angle	60°
Measuring light spot	9mm × 15mm
Minimum test area	20mm × 10mm
Measuring range	0-1000GU
Resolution	0.1GU
Repeatability	0-120GU: ±0.2GU; 120-1000GU: ±0.2%
Reproducibility	0-120GU: ±0.5GU; 120-1000GU: ±0.5%
Zero error	0.1GU
Indication error	0-120GU: ±1.5GU; 120-1000GU: ±1.5%
Display	192 × 64
Data interface	USB
Power supply	Rechargeable lithium 3.7V@1000mAh
Charging port	USB (Type-C)
Dimensions	102 × 35 × 51mm
Weight	About 300g
Languages	Simplified Chinese, English
Operating environment	10~45°C, 0~85%RH (no condensation)
Storage environment	-10~60°C, 0~85%RH (no condensation)

APPLICATIONS

Ceramics, PC plastics, marble and car paint.

Source: linshangtech.com product page · www.linshangtech.com/product/ls192-gloss-meter.html. Specifications are the manufacturer's and may change without notice. Images indicative. E&OE.