



Product data sheet

Power tools for trade & industry

Line Laser

GLL 18V-120-33 CG



Unstoppable 18V line laser for high precision in tough conditions

The most important data

Working range with receiver	radius up to 120 m
Working range	radius up to 35 m
Accuracy	± 0.3 mm/m

Order number 0 601 065 100

Technical data

Additional data

Tripod thread	1/4", 5/8"
Battery voltage	18.0 V, 12.0 V
Laser diode	500 – 540 nm, < 10 mW
Operating temperature	-10 – 40 °C
Storage temperature	-20 – 70 °C
Laser class	2
Working range	radius up to 35 m
Working range with receiver	radius up to 120 m
Accuracy	± 0.3 mm/m
Self-levelling range	$\pm 4^\circ$
Levelling time	3 s
Dust and splash protection	IP65 (except for the battery or battery adapter)
Power supply	18 V Li-ion battery, 12 V Li-ion battery, 4 x 1.5 V LR14 (C)
Operating time (max.)	20 h (18V 4Ah Li-ion), 8 h (12V 2Ah Li-ion), 8 h (4 x C, energy saving mode) in 3-line mode
Weight, approx.	1.3 kg
Colour of laser line	green
Projection	3 x 360° line

Compatible laser receivers	LR 7
Weight with 4.0 Ah battery	1.9 kg
Weight with alkaline batteries	1.8 kg
Working range, value	35 m
Working range with receiver, value	120 m

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Easily switch between 18V, 12V, and alkaline C-cell power sources to avoid downtime
- Rubber-enforced housing and laser windows, and an IP65 rating for peace of mind on the toughest jobsites
- Secure mounting and precise work are made easy thanks to the integrated mount with strong magnets and pivot fine adjustment



PROTECTED TOOLS
Impact | Water | Dust

